

# CONTENTS

Abstract .....	1
Introduction .....	1
Purpose and Scope .....	2
Study Area .....	2
Model Description .....	2
Description of Simulated Water-Management Alternatives .....	4
Effects of Water-Management Alternatives on Streamflow .....	11
Summer of 1993 Hydrographs .....	12
Flow Duration .....	14
Low-Flow Frequency .....	18
1-Day Low Flow .....	19
7-Day Low Flow .....	22
30-Day Low Flow .....	24
Summary and Conclusions .....	29
References .....	30

## FIGURES

1,2. Maps of the Ipswich River Basin, Massachusetts, showing:	
1. Municipalities, drainage network, and stream-gaging stations .....	3
2. Water-supply withdrawal sites and hypothetical wastewater-return flow sites in the headwaters .....	5
3,4. Graphs showing:	
3. Daily streamflow-depletion rates calculated for alternative withdrawal rates at selected model reaches in the Ipswich River Basin .....	7
4. Example of the streamflow depletion at model reach 8 limited by a special action developed for the Hydrological Simulation Program—Fortran (HSPF) when model reach 19 is below 22 cubic feet per second .....	9
5. Box plot of total precipitation during July and August 1961 through 1995 relative to total precipitation during July and August 1993 .....	12
6–9. Graphs showing:	
6. Daily flow at model reach 8 simulated under management alternatives for (A) water supply, (B) wastewater, and (C) combined water supply and wastewater, June through October 1993 .....	13
7. Cumulative-streamflow volume as a percentage of cumulative-streamflow volume under no withdrawals in relation to cumulative withdrawals as a percentage of the actual withdrawals in model reach 8, July 1 through August 31, 1993 .....	14
8. Daily flow at model reach 19 simulated under management alternatives for (A) water supply, (B) wastewater, and (C) combined water supply and wastewater, June through October 1993 .....	15
9. Flow-duration curves of simulated daily-mean streamflow at model reach 8 and 19 under management alternatives for (A) water supply, (B) wastewater, and (C) combined water supply and wastewater, 1961–95 .....	17
10–15. Graphs showing Log-Pearson type III low-flow frequency curves for:	
10. 1-day annual minimum daily-mean streamflow simulated under management alternatives for (A) water supply, (B) wastewater, and (C) combined water supply and wastewater, model reach 8, 1961–95 .....	20

11. 1-day annual minimum daily-mean streamflow simulated under management alternatives for (A) water supply, (B) wastewater, and (C) combined water supply and wastewater, model reach 19, 1961–95 .....	21
12. 7-day annual minimum daily-mean streamflow simulated under management alternatives for (A) water supply, (B) wastewater, and (C) combined water supply and wastewater, model reach 8, 1961–95 .....	23
13. 7-day annual minimum daily-mean streamflow simulated under management alternatives for (A) water supply, (B) wastewater, and (C) combined water supply and wastewater, model reach 19, 1961–95 .....	25
14. 30-day annual minimum daily-mean streamflow simulated under management alternatives for (A) water supply, (B) wastewater, and (C) combined water supply and wastewater, model reach 8, 1961–95 .....	26
15. 30-day annual minimum daily-mean streamflow simulated under management alternatives for (A) water supply, (B) wastewater, and (C) combined water supply and wastewater, model reach 19, 1961–95 .....	28

## TABLES

1. Water-management alternatives simulated with the Hydrologic Simulation Program—Fortran (HSPF) of the Ipswich River Basin, Massachusetts .....	6
2. Average 1989–93 withdrawal rates and a 50-percent reduction in withdrawal rates from the Ipswich River Basin from May and October for the towns of Wilmington and Reading .....	10
3. Hypothetical wastewater-return flow rates and associated model reach of the return flow in the Town of Wilmington. ....	11
4. Median 1-, 7-, and 30-day annual low-flow at model reaches 8 and 19, simulated under water-management alternatives, Ipswich River, 1961–95 .....	18

## CONVERSION FACTORS

### CONVERSION FACTORS

	Multiply	By	To obtain
cubic foot per second (ft <sup>3</sup> /s)		0.02832	cubic meter per second
gallon per day (gal/d)		0.003785	cubic meter per day
million gallons (Mgal)		3,785	cubic meter
million gallons per day (Mgal/d)		0.04381	cubic meter per second
square mile (mi <sup>2</sup> )		259.0	hectare
square mile (mi <sup>2</sup> )		2.590	square kilometer